

GIR

Rotatori industriali

Industrial rotator **EN** | **FR** Rotateur industriel
Industrierotatoren **DE** | **ES** Rotadore industriale

GIR12



Max. axial load static: ± 250 kN
Max. axial load dynamic: ± 80 kN
Max radial load: not recommended
Deflection: not recommended
Torque: 2000 Nm
Weight: 85 kg

GIR12-01



Max. axial load static: ± 250 kN
Max. axial load dynamic: ± 80 kN
Max radial load: not recommended
Deflection: not recommended
Torque: 2000 Nm
Weight: 82 kg

GIR25



Max. axial load static: ± 450 kN
Max. axial load dynamic: ± 160 kN
Max radial load: not recommended
Deflection: not recommended
Torque: 3500 Nm
Weight: 143 kg

GIR25-01



Max. axial load static: ± 450 kN
Max. axial load dynamic: ± 160 kN
Max radial load: not recommended
Deflection: not recommended
Torque: 3500 Nm
Weight: 143 kg

GIR25-02



Max. axial load static: ± 450 kN
Max. axial load dynamic: ± 160 kN
Max radial load: not recommended
Deflection: not recommended
Torque: 3500 Nm
Weight: 143 kg

GIR25-04



Max. axial load static: ± 450 kN
Max. axial load dynamic: ± 160 kN
Max radial load: not recommended
Deflection: not recommended
Torque: 3500 Nm
Weight: 143 kg

